
Index

A

"A" cable, 197
Accelerated Graphics Port (AGP), 97–98
accelerated hub architecture, 91
Accelis (tape media), 458
access time, 14
active cluster, 469
Active Directory, 46, 368
active termination, 203
actual power, 141
actuator mechanism, 176
adapter cards, 578–579
adapters, 265–266. *See also* network adapters
adapter teaming, 313
Adaptive Fault Tolerance (AFT) network adapter, 313–315
Adaptive Load Balancing (ALB) network adapter, 313–315
Address Resolution Protocol (ARP), 293
Advanced Intelligent Tape (AIT), 455
Advanced Technology Attachment (ATA), 14
advanced technology (AT) bus, 92
Advanced Transfer Cache (ATC), 99–100
Aelita Even Management, 549
AFT. *See* Adaptive Fault Tolerance (AFT) network adapter
aggregation, 313–315, 527
AGP. *See* Accelerated Graphics Port (AGP)
air conditioning, 53–55, 56–58. *See also* temperature
air filter, drive head, 175–176
airflow
 server maintenance and, 475–476
 server rack and, 147–148
 for UPS system, 143
air quality, server and, 55–56
AIT. *See* Advanced Intelligent Tape (AIT)
ALB. *See* Adaptive Load Balancing (ALB) network adapter
alerts, performance, 506–509
AMD processor, 88, 98
AMD Sledgehammer, 88, 104
American Megatrends Inc.(AMI), 111, 563–564, 569
American Power Conversion (APC), 139, 143
analog modem pool, 317
Andrews, Jean, 88, 573
Apache (web services), 413
APC. *See* American Power Conversion (APC)
APC Silicon DP2500E (UPS system), 142
apparent power, 141
applications
 distribution of, 521
 movement of, 515
 operation of, 515–516
applications access
 database applications, 16
 email services, 16
 network management software, 16–17
 remote access, 17
 virtual private networks, 17
application server mode, 566
application servers, network operating system, 421
arbitration method, 195

archive files, 524
"A" record, 345
ARP. *See* Address Resolution Protocol (ARP)
asymmetric port aggregation, 313–315
AT. *See* advanced technology (AT) bus
ATA. *See* Advanced Technology Attachment (ATA)
ATA (AT Attachment). *See* IDE interface
ATA cable, 186–189
ATA Packet Interface (ATAPI), 183
ATAPI. *See* ATA Packet Interface (ATAPI)
ATC. *See* Advanced Transfer Cache (ATC)
ATX Power Connection, 264
ATX power supply connector, 263
authentication, in general, 8–11
autoloaders, 451
Award Software, BIOS programming, 111

B

backbone
 hubs and, 296
 network and, 284, 285
back-end applications, 15
backprobing, defined, 263
back side bus, 99
Backup Domain Controller (BDC), 365
backup generator, 63
backups, 448–467
 automated tape solutions, 451–459
 in general, 451–452
 maintenance of, 458–459
 types of, 452–458

- for client-server networks, 6
 - hardware for, 448–450
 - records of, 467
 - server upgrade and, 237
 - software for, 459–460
 - storing and securing, 460–461
 - types of, 461–467
 - copy, 462
 - daily, 462
 - differential, 462
 - incremental, 462–463
 - normal, 461
 - six-cartridge, 465–466
 - strategy for, 463–464
 - Tower of Hanoi, 466–467
 - backup window, 449
 - ballast, rack, 146
 - bandwidth
 - bus interfaces and, 92–93
 - defined, 40–41
 - network, 284, 285
 - baseline
 - bottleneck and, 509–510
 - Logon Server and, 511
 - monitoring, 510–511
 - performance, 233
 - basic input/output system (BIOS)
 - CMOS, protecting, 113–114
 - CMOS settings, accessing, 112–113
 - defined, 85
 - processor upgrading and, 245
 - recovering, 260–261
 - server, recovering, 260–261
 - server, upgrading, 235, 259–260
 - settings, common, 114–115
 - updating, 259–260
 - battery
 - CMOS and, 111
 - CMOS protection and, 113
 - electrostatic discharge and, 244
 - UPS
 - failover for, 139–140
 - in general, 136–137
 - site preparation and, 141–142
 - BDC. *See* Backup Domain Controller (BDC)
 - Belkin (cable vendor), 306
 - bend radius, 552
 - Berkeley Internet Name Domain (BIND), 398
 - Best Power website, 143
 - BIND. *See* Berkeley Internet Name Domain (BIND)
 - bio-recognition, security and, 73
 - BIOS. *See* basic input/output system (BIOS)
 - blind connector mating, 198
 - blue screen of death (BSOD), 544, 569
 - boot. *See also* installation
 - hard disks, 575
 - unbootable server, 569–571
 - Bootstrap Protocol (BootP), 390, 393
 - bottleneck
 - defined, 509–510
 - network performance and, 527–528
 - verification of, 233
 - boundaries, security, 12
 - bridges, 298–299
 - BSOD. *See* blue screen of death (BSOD)
 - buffer cache, 14
 - buffered memory, 110
 - bulk erase, 458
 - bus
 - accelerated hub architecture, 91
 - chipset function, 87–88
 - clock frequency, 86–87
 - hierarchical bus, 88–90
 - front side bus, 89
 - ISA bus, 89
 - PCI bus, 89
 - network topology and, 284–285
 - speed, mainframe servers and, 26
 - bus interfaces
 - Accelerated Graphics Port, 97–98
 - EISA, 92
 - ISA, 92
 - PCI, 92–97
 - bus mastering, 94
 - intelligent input/output, 96–97
 - interrupts, 94
 - PCI hot swap, 95
 - PCI-X, 93–94
 - peer PCI bus, 95–96
- ## C
- cable, ATA, 186–189
 - cable labeling, 546
 - cable management, 152–155
 - cable management arm (CMA), 146, 152–154
 - cable select, 190
 - cables, SCSI, 196–199, 577
 - cable tray, 154
 - cabling, network. *See* network cabling
 - cache
 - buffer, 14
 - defined, 13
 - memory, processor and, 99–100
 - RAID, 210
 - Caldera Linux, 349
 - capacity planning, 512–513
 - card scanners, 73
 - Carrier Sense Multiple Access with Collision Detection (CSMA/CD), 296
 - cartridge labels, 467
 - catalog, backup, 467
 - CD. *See* Collision Detection (CD); compact disc
 - CD-ROM, 476
 - Celeron processor, 103
 - centralized management, 18
 - challenge handshake authentication protocol (CHAP), 416
 - Channel Service Unit/Digital Service Unit (CSU/DSU), 300
 - chassis
 - electrostatic discharge and, 242
 - heavy duty, 24
 - power supply replacement and, 265
-

chipset function, 87–88
 circuit breaker, 66–67
 CISC. *See* complex instruction set computing (CISC)
 "Clean power", 64
 clock frequency, 86–87
 clock speed, 97
 cloning software, 572
 clustering
 devices on rack, 151–152
 FAT and, 179
 implementation, 515
 network, 18–19
 server availability and redundancy and, 468–470
 CMA. *See* cable management arm (CMA)
 CMOS. *See* complimentary metal oxide semiconductor (CMOS)
 CName record, 399
 cold sites, 478
 collision, defined, 291
 Collision Detection (CD), 296
 collision domain, 291, 299
 command queuing, 193
 compact disc (CD), 449, 544
 Compaq
 IntelliSafe, 184
 PCI hot swap and, 95
 website for rack configuration, 149
 Compaq ProLiant 8000, 239
 compatibility, 93
 compiler, defined, 103
 complex instruction set computing (CISC), 22
 complimentary metal oxide semiconductor (CMOS)
 error and, 261
 in general, 111
 protecting, 113–114
 settings, accessing, 112–113
 components, 235–236, 240–245.
 See also hardware
 compression removal, 514

CompTIA Server+ Exam Blueprint, 240
 Computer Associates Unicenter TNG, 239, 472, 474
 connection rate, network, 285
 connection speed, 49–50
 connections, physical, 552–553
 network cabling, 552
 connectivity utilities, 556–558
 connectors, SCSI, 196–199
 console, defined, 158
 container, defined, 341
 convergence, delayed, 427
 convergence, rapid, 428
 conversion, NOS to NOS, 47
 cooling. *See also* temperature
 for hard drives, 176
 processor, 250–252
 server rack installation and, 147–148
 cooling fans
 for PC servers, 24
 for server, 54–56
 for Xeon processor, 101
 copy backup, 462
 cost effectiveness
 of fibre channel, 210
 of mainframe servers, 25
 of processors and memory, 20
 savings, efficiency, and productivity, 21
 server need and, 40–41
 of storage, 19
 CPU fan, 250–252
 CPU utilization, 501–502
 CRC. *See* cyclical redundancy check (CRC)
 crimp tool, modular plug, 307
 crossover cables, 306
 crosstalk, 302
 CSMA/CD. *See* Carrier Sense Multiple Access with Collision Detection (CSMA/CD)

CSU/DSU. *See* Channel Service Unit/Digital Service Unit (CSU/DSU)
 cutters, diagonal, 307–308
 cyclical redundancy check (CRC), 194
D
 daemons, 390
 daily backup, 462
 daisy chain, 204
 DAT. *See* digital audio tape (DAT)
 database applications, 16
 Data bus, defined, 13
 datacenter, 60, 145
 Data Clean Corporation, 55
 data collection facility, 498
 data rate, bandwidth and, 284
 DDR SDRAM. *See* double data rate SDRAM (DDR SDRAM)
 Dean, Tamara, 288, 556
 Debian Linux, 349
 dedicated application, 421
 defragmentation, 523–524
 dehumidification system, 57
 Dell, 95, 149
 density, server rack and, 24–25, 144
 Desktop Management Interface (DMI), 425
 device grouping, 151–152
 device ID, 577
 devices, adding, 238
 df command, 499
 DHCP. *See* Dynamic Host Configuration Protocol (DHCP)
 diagnostic tools, 555–565
 connectivity utilities, 556–558
 network cable diagnostic devices, 555–556
 operating system utilities, 559–562
 Linux, 560–561
 Microsoft Windows 2000, 562

- Microsoft Windows
 - NT 4.0, 561
 - Novell NetWare, 560
 - OS/2, 559
 - system and hardware diagnostic utilities, 562–565
 - dial-up, modem pool and, 316–317
 - differential backup, 462
 - digital audio tape (DAT), 454–455
 - Digital Equipment Corporation (DEC) PDP-1, 26
 - digital linear tape (DLT), 455–456
 - digital modem pool, 317
 - digital multimeter (DMM), 261–264
 - DIMMs. *See* dual inline memory modules (DIMMs)
 - Direct Memory Address (DMA), 238
 - directory service, 338–339
 - disaster planning, 447–479
 - backups, 448–467
 - automated tape solutions, 451–459
 - in general, 451–452
 - maintenance of, 458–459
 - types of, 452–458
 - hardware for, 448–450
 - records of, 467
 - software for, 459–460
 - storing and securing, 460–461
 - types of, 461–467
 - copy, 462
 - daily, 462
 - differential, 462
 - incremental, 462–463
 - normal, 461
 - six-cartridge, 465–466
 - strategy for, 463–464
 - Tower of Hanoi, 466–467
 - disaster recovery plan, 476–479
 - alternate sites, using, 477–478
 - cold sites, 478
 - hot sites, 478
 - in general, 476–477
 - site management, 478–479
 - in general, 67–69, 447–448
 - high server availability and redundancy, 468–571
 - failover, 470
 - in general, 468–470
 - spare parts, 470–471
 - server management and maintenance, 472–476
 - physical care, 475–476
 - software for, 472–474
 - SNMP settings, 471–472
 - disaster recovery plan (DRP), 476–479
 - alternate sites, using, 477–478
 - cold sites, 478
 - hot sites, 478
 - in general, 476–477
 - discovery broadcast, 391
 - disk errors, 525
 - disk mirroring, 211–212
 - disk platter, 175
 - disk striping, 210–211
 - distributed application, 421
 - DLT. *See* digital linear tape (DLT)
 - DMA. *See* Direct Memory Address (DMA)
 - DMI. *See* Desktop Management Interface (DMI)
 - DMM. *See* digital multimeter (DMM)
 - DNS. *See* Domain Name Service (DNS); Domain Name System (DNS)
 - documentation, 543, 580
 - Domain Name Service (DNS), 394–401
 - name resolution, 394–396
 - records, 398–400
 - servers, types of, 400–401
 - zones, 397–398
 - Domain Name System (DNS), 8
 - double data rate SDRAM (DDR SDRAM), 107–108
 - double transition (DT)
 - clocking, 195
 - DPNS. *See* Dynamic DNS (DDNS)
 - drive configuration (SCSI ID and LUN), 203–206
 - SCSI ID assignment, 205–206
 - topology, 204
 - drive connections, 264
 - drive heads, 175–176
 - driver
 - installation of, 544–545
 - operation verification, 515–516
 - for server upgrade, 235–236
 - DRP. *See* disaster recovery plan (DRP)
 - dual inline memory modules (DIMMs)
 - in general, 105–106
 - memory installation and, 257–258
 - memory upgrade and, 253–254, 255–256
 - durability, mainframe servers, 26
 - dust, 55, 475–476
 - Dynamic DNS (DDNS), 356, 400
 - Dynamic Host Configuration Protocol (DHCP), 43, 390–393
 - dynamic RAM (DRAM), 104
- ## E
- ECC. *See* error correcting code (ECC)
 - EDO. *See* Extended Data Out (EDO)
 - EEPROM. *See* electrically erasable programmable read-only memory (EEPROM)
 - EIA. *See* Electronic Industries Alliance (EIA) units
 - EIDE (ATA-2), 183–184
 - 80-conductor cable, 188–189
-

EISA. *See* Extended ISA (EISA) bus
 electrically erasable programmable read-only memory (EEP-ROM), 111
 electromagnetic interference (EMI), 65–67
 Electronic Industries Alliance (EIA) units, 144–145
 electrostatic discharge (ESD)
 flooring and, 59–60
 in general, 56–57
 server upgrade, performing, 241–245
 chassis, touch, 242
 grounding kit, use, 243
 other tips for, 244–245
 power, unplug, 242–243
 email
 applications access, 16
 company broadcast, 234
 protocols, 407–408
 server applications and requirements, 408–410
 server functions and, 8
 troubleshooting and, 581
 Emergency Management Port, 473
 EMI. *See* electromagnetic interference (EMI)
 encryption removal, 514
 Enhanced A+ Guide to Managing and Maintaining Your PC (Andrews), 88, 573
 Enhanced IDE (EIDE) interface, 14
 enterprise, defined, 46
 Environmental Protection Agency (EPA), 68
 EPIC. *See* Explicitly Parallel Construction (EPIC)
 equipment, improvement of, 527
 equipment, network. *See* network equipment
 error correcting code (ECC), 110, 254

errors. *See* troubleshooting and problem determination
 ESD. *See* electrostatic discharge (ESD)
 Ethernet
 bridges, 298–299
 Fast Ethernet, 297
 full-duplex Ethernet, 297
 in general, 295–297
 Gigabit Ethernet, 298
 network, hybrid topologies, 288
 network interface card and, 528
 network media access methods, 295–297
 switches, 299–300
 Token Ring network and, 295
 event logs, 473, 547–549
 expandability, 24, 206
 Explain button, 505
 Explicitly Parallel Construction (EPIC), 104
 Extended Data Out (EDO), 105
 Extended ISA (EISA) bus, 92
 extended partition, 178

F

failback, 470
 failover, 41, 470
 fans
 for CPU, 250–252
 for PSU, 133, 134
 for server rack, 147–148
 troubleshooting and, 554
 FAQs, 581
 Fast Ethernet, 297
 Fast SCSI, 193
 FAT. *See* File Allocation Table (FAT/FAT32)
 fault tolerance, 18
 fax boards, 418–419
 fax services, 418–419
 FC. *See* fibre channel (FC)
 FC-AL. *See* Fibre Channel Arbitrated Loop (FC-AL)
 FDISK, 361
 FDISK, MS-DOS, 177

fibre optic network cabling, 311–312
 fibre channel (FC), 208–210
 Fibre Channel Arbitrated Loop (FC-AL), 208
 field replaceable unit (FRU), 115
 troubleshooting, 573–579
 adapter cards, 578–579
 hard disks, 575–576
 memory, 574–575
 power supply, 574
 processor, 579
 SCSI and RAID, 576–578
 cabling, 577
 device ID, 577
 RAID, 578
 termination, 576
 File Allocation Table (FAT/FAT32), 179, 361–364
 file archives, 524
 file distribution, 524
 file server, 6–7
 file systems, 179–182
 FAT/FAT32, 179
 HPFS, 180–181
 Linux/UNIX, 181
 NetWare, 181–182
 NT File System, 180
 File Transfer Protocol (FTP) server, 50
 fire detection and suppression, 67–68
 firewall, 21, 428–429
 FireWire bus, 185
 "5-4-3 rule", Ethernet and, 297
 flash BIOS, 111, 112, 259
 floods, server and, 68–69
 flooring, server room, 58–62
 floppy drives, 476
 Flotron (processor extraction tool), 250
 forced perfect termination (FPT), 203
 FORMAT command, 177–178
 Fox and Hound device, 556

FPT. *See* forced perfect termination (FPT)
 fragmentation, hard disk, 523–524
 front-end applications, 15
 front side bus, 89
 FRU. *See* field replaceable unit (FRU)
 FTP server. *See* File Transfer Protocol (FTP) server
 full-duplex Ethernet, 297

G

Gateway Services, 45–46
 GDISK, Symantec, 178
 generator kick, 139
 GFS. *See* Grandfather-Father-Son (GFS) backup strategy
 Gigabit Ethernet, 298
 GMCH. *See* Graphics Memory Controller Hub (GMCH)
 GNOME, graphical user interface, 347, 354
 GNOME System Monitor, 500–501
 Grandfather-Father-Son (GFS) backup strategy, 463–464
 graphics, 97–98
 Graphics Memory Controller Hub (GMCH), 91
 gray code, defined, 176
 grounding kit, 243–244
 groups, authentication of, 9–10

H

hackers, server security and, 72
 halon (fire suppressant), 68
 hard disk. *See also* disaster planning; performance monitoring and optimization, hard disk backup software for, 459–460
 hot-pluggable, 23
 installing, 238–239
 NetWare and partitioning of, 342–344
 performance, 13–14, 189
 troubleshooting, 575–576

hard disk interfaces
 fibre channel, 208–210
 file systems, 179–182
 FAT/FAT32, 179
 HPFS, 180–181
 Linux/UNIX, 181
 NetWare, 181–182
 NT File System, 180
 in general, 173–174
 hard disk components, 174–176
 disk platters, 175
 drive heads, 175–176
 IDE interface, 182–191
 ATA-1, 183
 ATA-2, 183–184
 ATA-3, 184
 ATA-4, 184–185
 ATA-5, 185–186
 ATA-6, 186
 ATA cable, 186–189
 in general, 182–183
 master, slave, and cable select, 189–190
 pros and cons of, 190–191
 partitions and logical drives, 177–179
 creating partition, 177–178
 logical drives, 178–179
 SCSI configuration, 196–207
 drive configuration (SCSI ID and LUN), 203–206
 SCSI ID assignment, 205–206
 topology, 204–205
 pros and cons of, 206–207
 SCSI cables and connectors, 196–199
 SCSI termination, 201–203
 signaling, 199–201
 high voltage differential, 199–200
 low voltage differential, 200–201
 single-ended, 199
 SCSI interface, 192–196
 SCSI-1, 192–193
 SCSI-2, 193
 SCSI-3, 193–196
 SPI-2, 194
 SPI-3, 194–195
 SPI SCSI-3 Parallel Interface, 194
 Ultra160 and Ultra160+, 195–196
 hard drives, 53, 135
 hardware
 for backups, 448–450
 diagnostic utilities for, 562–565
 installation of, 544–545
 inventory for, 239–240
 RAID, 215
 for server upgrade, 235–236
 spare parts, 470–471
 troubleshooting and, 579
 hardware requirements
 for Linux, 349–350
 for Microsoft Windows 2000, 370
 for Microsoft Windows NT Server, 361
 for network operating system, 336
 for OS/2, 356–357
 head crash, 175
 heat sink, 250–252
 helical scanning, 454–455
 Hewlett Packard
 on backups, 448
 OpenView, 239
 PCI hot swap and, 95
 website for rack configuration, 149
 hierarchical bus, 88–90
 front side bus, 89
 ISA bus, 89
 PCI bus, 89
 Hierarchical Storage Management (HSM), 449
 high byte, 203
 High Performance File System (HPFS), 180–181
 host, 2, 556–558
 host adapter, 182, 204–205, 214

host name record, 345
 hot fix, 345
 hot sites, 478
 hot spare, 237, 471
 hot-swappable PSU, 132, 133, 265–266
 HPFS. *See* High Performance File System (HPFS)
 HSM. *See* Hierarchical Storage Management (HSM)
 hub
 accelerated hub architecture, 91
 full-duplex Ethernet and, 298
 local area network and, 2
 network, 296
 network performance and, 527–528
 HVAC system
 flooring and, 59
 for server, 55–57
 UPS systems and, 143
 HVD termination, 203
 hybrid network topology, 288

I

IBM. *See also* OS/2
 HPFS and, 180–181
 mainframe pioneer, 25
 OS/2, System Performance Monitor/2, 498
 Predictive Failure Analysis of, 184
 RISC processor, 22
 website for rack configuration, 149–150
 IBM Tivoli, 239, 472
 IBM WebSphere, 341
 IDE interface. *See* Integrated Drive Electronics (IDE)
 interface
 IEEE. *See* Institute for Electrical and Electronic Engineers (IEEE)
 IEEE Recommended Practice for Powering and Grounding Sensitive Electronic Equipment, 63

IIS. *See* Internet Information Server (IIS)
 IMAP. *See* Internet Message Access Protocol (IMAP)
 incremental backup, 462–463
 Industry Standard Architecture (ISA) bus, 89, 92
 Innoculan, 573
 input/output (I/O)
 Controller Hub, 91
 IDE/ATA and, 191
 performance, 96–97
 port, 238
 inrush power, 134, 158, 205
 installation
 of Linux, 350–354
 of Microsoft Windows 2000, 370–372
 of Microsoft Windows NT Server, 361–366
 of network operating system, 336
 of OS/2, 357–358
 instances, 504
 Institute for Electrical and Electronic Engineers (IEEE)
 802.3 standard, 296
 802.3u (Fast Ethernet), 297
 802.5 standard, 295
 Gigabit Ethernet, 298
 server room and, 63
 Integrated Drive Electronics (IDE) interface, 182–191
 ATA-1, 183
 ATA-2, 183–184
 ATA-3, 184
 ATA-4, 184–185
 ATA-5, 185–186
 ATA-6, 186
 ATA cable, 186–189
 cables, 553
 in general, 182–183
 master, slave, and cable select, 189–190
 pros and cons of, 190–191
 Integrated Services Digital Network (ISDN), 48

Intel
 hub architecture, 91
 processors, 98
 Itanium, 103–104
 Xeon and Pentium, 100–103
 website for chipsets, 88
 intelligent hub, 296
 Intelligent Input/Output (I2O), 96–97
 interface. *See* hard disk interfaces;
 Integrated Drive Electronics (IDE) interface; Small Computer Systems Interface (SCSI), interface
 interface, disk drive, 14
 interleaving, 108–110
 Internet (IP) Address, 290
 ARP and, 293
 connectivity and, 556–558
 IPCONFIG utility, 292–293
 network performance and, 526–527
 Ping and, 291–292
 subnetting network and, 291
 Internet Information Server (IIS), 413
 Internet Message Access Protocol (IMAP), 407
 Internetwork Packet Exchange/Sequence Packet Exchange (IPX/SPX), 45–46, 289, 345
 interrupt request (IRQ), 94, 238
 inter-site server placement, 50–51
 intra-site communication, 49–50
 inventory, for server upgrade, 239–240
 I/O. *See* input/output (I/O)
 IP Address. *See* Internet (IP) Address
 IPX/SPX. *See* Internetwork Packet Exchange/Sequence Packet Exchange (IPX/SPX)
 IRQ. *See* interrupt request (IRQ)
 ISA. *See* Industry Standard Architecture (ISA) bus

ISDN. *See* Integrated Services Digital Network (ISDN)
 iterative query, 395–396

J

Journalled File System (JFS), 180–181, 356

K

Kernighan, Brian, 347
 keyboard, 158–160
 keypad, 73
 KVM. *See* single keyboard, video display, and mouse (KVM)

L

L1 cache, 99
 L2 cache, 99–100
 LAN. *See* local area network (LAN)
 LDAP. *See* Lightweight Directory Access Protocol (LDAP)
 level 2 tunneling protocol (L2TP), 415
 leveling screw, 146
 licensing mode, 364–365
 Liebert air-conditioning system, 57–58, 143
 Lightweight Directory Access Protocol (LDAP), 339
 Linear Tape Open-Cartridge Memory (LTO-CM), 456
 Linear Tape Open (LTO) technology, 456–457
 line conditioner, defined, 140
 line interactive, UPS type, 137
 line protocols, 414–415
 link aggregation, 315, 527
 Linux
 AMD Sledgehammer, 104
 diagnostic tools, 560–561
 Filesystem Hierarchy Standard, 181
 hardware requirements for, 349–350
 installation of, 350–354
 performance monitoring and optimization of, 499–501
 proper shutdown of, 354–355
 Linux Caldera, 349
 Linux Loader (LILO), 350
 LMHOSTS file, 402–403
 load balancing, 41
 load equipment, defined, 136
 local area network (LAN). *See also* network cabling; networking with modem pool
 defined, 2–3
 intra-site server placement and, 49–50
 ring topology, 285–287
 server as firewall and, 428–429
 locking plugs, 157
 log files, 467
 Logging Facility, 498
 logical drives, 178–179
 logical network topology, 284
 logical unit number (LUN), 206
 Logical Volume Manager (LVM), 356
 log off, computer, 72
 Logon Server data, 511–512
 log records, troubleshooting, 543–546
 cable labeling, 546
 hardware and drivers, installing, 544–545
 new peripherals, adding, 543–544
 server interaction, 545
 server purpose, 545–546
 server work statement, 546
 software, installing, 544
 updates or upgrades, installing, 544
 user identification, 546
 logs, 74, 506–509
 LTO. *See* Linear Tape Open (LTO) technology
 LTO-CM. *See* Linear Tape Open-Cartridge Memory (LTO-CM)

LUN. *See* logical unit number (LUN)
 LVD termination, 203
 LVM. *See* Logical Volume Manager (LVM)

M

MAC. *See* Media Access Control (MAC)
 magic packet, 565
 mail services, 406–407
 mainframe servers
 bus speed, 26
 cost, 25
 durability, 26
 memory, 26
 processors, 25–26
 size, 25
 storage, 26
 managed hub, 296
 Management Information File (MIF), 425
 Mandrake Linux, 349
 mapping, 337
 master drive, 189–190
 MAU. *See* multistation access unit (MAU)
 McAfee VirusScan, 573
 mean time between failure (MTBF), 26, 131, 176
 Media Access Control (MAC)
 address, 289, 293, 527
 media access method, 294.
 See also network media access method
 megahertz, 86–87, 98
 member server, 365
 memory. *See also* performance monitoring and optimization, memory
 address, 238
 buffered and registered, 110
 cache memory
 L1 cache, 99
 L2 cache, 99–100
 core dump, 342

- DDR SDRAM, 107–108
- DIMM modules, 105–106
- direct memory access, 97
- error correcting code, 110
- Extended Data Out and, 105
- hard disk utilization and, 233
- interleaving, 108–110
- leak, 518, 521
- mainframe servers and, 26
- RDRAM, 107
- SDRAM, 106
- server processor and, 101
- SIMM modules, 104–105
- troubleshooting, 574–575
- upgrading, 253–259
 - identification of, 254–256
 - installation of, 257–259
- mezzanine bus, 102
- MGE website, 143
- MHz (megahertz), 86–87, 98
- Microsoft Active Directory, 46, 368
- Microsoft IPCONFIG utility, 292–293
- Microsoft Knowledge Base website, 548
- Microsoft Management Console (MMC), 505–509
 - in general, 505–506
 - performance logs and alerts, 506–509
 - System Monitor, 506
- Microsoft Systems Management Server, 239
- Microsoft Windows
 - Internet Security and Acceleration (ISA) Server, 429
 - upgrades and, 337–338
 - UPS and users in, 136
- Microsoft Windows 2000
 - ATA-2 and, 184
 - backup utility, 459
 - boot floppy creation, 571
 - diagnostic tools, 562
 - disk defragmentation, 523–524
 - monitoring, 505–509
 - notifying operating system, 252–253
 - peer-to-peer networks and, 3–4
 - performance logs and alerts, 506–509
 - Performance Monitor, 496–497, 515–516
 - Proxy Server, 429
 - security boundaries of, 12
 - System Monitor, 506
 - Terminal Services, 566
- Microsoft Windows 2000
 - Advanced Server, 259
- Microsoft Windows 2000, configuring, 368–374
 - in general, 368–369
 - hardware requirements for, 370
 - installation of, 370–372
 - shutdown, proper, 373–374
 - swap-file space, 373
 - upgrade to, 372–373
 - versions, 369–370
- Microsoft Windows 2000 Professional, 520
- Microsoft Windows 2000 Server
 - Disk Management console, 179
 - TCP/IP configuration of, 290
 - upgrading to, 232–233
- Microsoft Windows 95/98
 - ATA-2 and, 184
 - creating a partition and, 177
 - peer-to-peer networks and, 3–4
- Microsoft Windows Computer Management Console, 567–569
- Microsoft Windows .NET, 546–548
- Microsoft Windows NT
 - ATA-2 and, 184
 - boot floppy creation, 570
 - diagnostic tools, 561
 - disk defragmentation, 523–524
 - memory installation and, 258
 - Microsoft Proxy Server, 429
 - notifying operating system, 252, 253
 - NTFS and, 180
 - peer-to-peer networks and, 3–5
 - performance monitoring and optimization, 503–504
 - process priority, 517
 - security boundaries of, 12
 - server interoperability and, 45–46
 - software RAID and, 215
- Microsoft Windows NT Server, configuring, 360–368
 - in general, 360–361
 - hardware requirements for, 361
 - installation of, 361–366
 - shutdown, proper, 367–368
 - swap-file space, 367
 - upgrade to, 366
- Microsoft Windows XP, 370
- midrange computer, 26
- MIF. *See* Management Information File (MIF)
- MIME. *See* Multipurpose Internet Mail Extensions (MIME)
- minicomputer, 26
- MMC. *See* Microsoft Management Console (MMC)
- modem pool. *See* networking with modem pool
- monitor cable, 153–154
- monitoring protocols, network operating system, 421–425
- motherboard architecture, 85–115
- bus
 - accelerated hub architecture, 91
 - chipset function, 87–88
 - clock frequency, 86–87
 - hierarchical bus, 88–90
 - front side bus, 89
 - ISA bus, 89
 - PCI bus, 89
- bus interfaces
 - Accelerated Graphics Port, 97–98
 - EISA, 92

- ISA, 92
 - PCI, 92–97
 - bus mastering, 94
 - I20 (intelligent input/output), 96–97
 - interrupts, 94
 - PCI hot swap, 95
 - PCI-X, 93–94
 - peer PCI bus, 95–96
 - CMOS, BIOS, and POST
 - BIOS, 111–115
 - CMOS, protecting, 113–114
 - CMOS settings, accessing, 112–113
 - settings, common, 114–115
 - CMOS, 111
 - in general, 85–86
 - memory
 - buffered and registered, 110
 - DDR SDRAM, 107–108
 - DIMM modules, 105–106
 - error correcting code, 110
 - Extended Data Out, 105
 - interleaving, 108–110
 - RDRAM, 107
 - SDRAM, 106
 - SIMM modules, 104–105
 - processors
 - 64-bit, 103–104
 - AMD Sledgehammer, 104
 - Intel Itanium, 103–104
 - cache memory, 99–100
 - in general, 98
 - server processors, 100–103
 - speed, 98
 - motherboard, processor
 - upgrading and, 245
 - motherboard upgrade, 519
 - mouse, 158–160
 - MS-DOS, 180, 563–565
 - MTBF. *See* mean time between failure (MTBF)
 - multihoming, 526–527
 - Multipurpose Internet Mail Extensions (MIME), 407
 - multistation access unit (MAU), 295
 - multithreading, 514
 - multi-user mode, 355
- N**
- name resolution, 394–396
 - NAS. *See* Network Access Server (NAS); network attached storage (NAS)
 - NDS. *See* Novell Directory Services (NDS)
 - NetBIOS, 401–403
 - NetBIOS Enhanced User Interface (NetBUEI), 289
 - NetBUEI. *See* NetBIOS Enhanced User Interface (NetBUEI)
 - NETSTAT, 294
 - NetWare. *See* Novell NetWare
 - network, 2, 48–51. *See also* performance monitoring and optimization, network
 - Network Access Server (NAS), 17
 - network adapters, 312–315
 - Adaptive Fault Tolerance, 313–315
 - Adaptive Load Balancing, 313–315
 - in general, 312–313
 - Link aggregation, 315
 - network attached storage (NAS), 208
 - network cable diagnostic devices, 555–556
 - network cabling, 301–312
 - 100BaseT, 311
 - 10BaseT, 311
 - crossover cables, 306
 - fiber optic, 311–312
 - RJ-45 connectors, how to cut and crimp, 306–310
 - RJ-45 pin assignments, 305
 - shielded twisted-pair, 302–303
 - thicknet, 301
 - thinnet, 301–302
 - troubleshooting, 552
 - unshielded twisted pair, 304–305
 - network device, 2
 - network diagram, 51–52
 - network equipment, 298–301
 - bridges, 298–299
 - routers, 300–301
 - switches, 299–300
 - Network+ Guide to Networks (Dean), 288, 556
 - networking with modem pool, 315–318
 - analog modem pool, 317
 - digital modem pool, 317
 - how it works, 316–317
 - partitioning and connecting, 318
 - network interface card (NIC)
 - defined, 43
 - NetWare installation and, 343
 - network performance and, 526–528
 - server as a router and, 426
 - upgrade of, 528
 - network management software, 16–17
 - network media access methods, 294–298
 - Ethernet, 295–297
 - Fast Ethernet, 297
 - full-duplex Ethernet, 297
 - Gigabit Ethernet, 298
 - Token Ring, 295
 - network operating system (NOS)
 - application servers, 421
 - client-server, 6–8
 - server interoperability, 43–47
 - server upgrade and, 235–236
 - network operating system (NOS), configuring, 335–375
 - configuration concepts, 336–338
 - hardware requirements for, 336
 - NOS installation, 336

- Novell NetWare, 338–347
 - characteristics of, 338–340
 - NetWare 5.1
 - installation of, 342–346
 - requirements for, 341–342
 - shutdown, proper, 347
 - swap-file space, 346
 - upgrade to, 346–347
 - OS/2, 355–359
 - in general, 355–356
 - hardware requirements for, 356–357
 - installation of, 357–358
 - shutdown, proper, 359
 - swap-file space, creating, 359
 - upgrade to OS/2 Warp, 359
 - versions, 356
 - shutdown, proper, 338
 - UNIX/Linux, 347–355
 - in general, 347–348
 - Linux
 - hardware requirements, 349–350
 - installation of, 350–354
 - shutdown, proper, 354–355
 - versions, 349
 - updating, 374–375
 - upgrades, performing, 337–338
 - virtual memory/swap files, 337
 - Windows 2000, 368–374
 - in general, 368–369
 - hardware requirements for, 370
 - installation of, 370–372
 - shutdown, proper, 373–374
 - swap-file space, 373
 - upgrade to, 372–373
 - versions, 369–370
 - Windows NT Server, 360–368
 - in general, 360–361
 - hardware requirements for, 361
 - installation of, 361–366
 - shutdown, proper, 367–368
 - swap-file space, 367
 - upgrade to, 366
 - network operating system (NOS), monitoring protocols, 421–425
 - Desktop Management Interface, 425
 - in general, 421–422
 - Simple Network Management Protocol, 422–425
 - network operating system (NOS), servers as a network device, 425–429
 - as a firewall, 428–429
 - as a router, 426–428
 - Open Shortest Path First protocol, 428
 - Router Information Protocol, 426–427
 - network operating system (NOS), services, 389–421
 - configuring RAS on a server, 416–417
 - Domain Name Service, 394–401
 - name resolution, 394–396
 - records, 398–400
 - servers, types of, 400–401
 - zones, 397–398
 - Dynamic Host Configuration Protocol, 390–393
 - lease process, 391–393
 - email protocols, 407–408
 - email server applications and requirements, 408–410
 - Fax services, 418–419
 - mail services, 406–407
 - remote access service, 413–416
 - in general, 413–414
 - protocols support, 414–415
 - security protocols, 416
 - Systems Network Architecture Server, 420–421
 - web and FTP servers, 410–413
 - configuring, 413
 - requirements, 410–413
 - Windows Internet Naming Service, 401–406
 - in general, 401–402
 - NetBIOS names, resolving, 402–403
 - proxy agent, 405–406
 - pull replication partners, 404
 - push/pull replication partner, 405
 - push replication partners, 404–405
 - replication, 403–404
 - network protocols, 289–294
 - IPX/SPX, 289
 - NetBEUI, 289
 - TCP/IP, 290–291, 291–294
 - Address Resolution Protocol, 293
 - Internet Address, 290
 - IPCONFIG utility, 292–293
 - NETSTAT, 294
 - packet internet groper, 291–292
 - subnetting the network, 291
 - TRACERT utility, 293–294
 - network resource, 3
 - network topologies, 284–288
 - bandwidth, 284
 - bus, 284–285
 - hybrid, 288
 - ring, 285–287
 - star, 287–288
 - network utilization, 41
 - newsgroups, 581
 - newsletters, 581
 - NIC. *See* network interface card (NIC)
 - NLMs. *See* Novell NetWare Loadable Modules (NLMs)
 - nodes, 285–287, 468
 - noncondensing relative humidity, 56
 - normal backup, 461
 - North Bridge chipset, 89–91, 95–96
 - Norton Antivirus, 573
 - Norton Ghost, 237
 - NOS. *See* network operating system (NOS)
 - notification of server upgrade, 234–235
-

Novell BorderManager, 21
 Novell Client, 47
 Novell Directory Services (NDS), 46–47, 339
 Novell Internet Caching System (ICS), 502
 Novell NetWare
 ATA-2 and, 184
 boot disks and, 571
 BorderManager, 429
 ConsoleOne, 339, 340
 diagnostic tools, 560
 file system, 181–182
 IPX/SPX and, 289
 performance monitoring and optimization of, 501–502
 server planning and, 45–46
 software RAID, 215
 Novell NetWare 3.12 server, 232–233
 Novell NetWare, configuring, 338–347
 characteristics of, 338–340
 NetWare 5.1
 hardware requirements for, 341–342
 installation of, 342–346
 shutdown, proper, 347
 swap-file space, 346
 upgrade to, 346–347
 Novell NetWare Loadable Modules (NLMs), 343
 Novell Storage Service (NSS) file system, 182
 NT File System (NTFS), 180, 361
 NTFS. *See* NT File System (NTFS)
 NTFSDOS utility, 72
 null modem cable, 89

O

Official Red Hat Linux Reference Guide, The, 350
 OLRP. *See* online retention period (OLRP)
 Oneac website, 143
 100Base T, network cabling, 297, 311

100Base TX technology, 287
 online/double conversion, UPS type, 137
 online retention period (OLRP), 451–452
 Open Shortest Path First (OSPF) protocol, 428
 operating systems. *See also* network operating system (NOS), configuring
 ATA-2 and, 184
 RAID and, 215
 server planning and, 43–47
 operating system utilities, 559–562
 Linux, 560–561
 Microsoft Windows 2000, 562
 Microsoft Windows NT 4.0, 561
 Novell NetWare, 560
 OS/2, 559
 optical disk, 449
 optimization. *See* performance monitoring and optimization
 OS/2
 diagnostic tools, 559
 System Performance Monitor/2, 498
 OS/2, configuring, 355–359
 in general, 355–356
 hardware requirements for, 356–357
 installation of, 357–358
 shutdown, proper, 359
 swap-file space, creating, 359
 upgrade to OS/2 Warp, 359
 versions, 356
 OS/2 Warp, 184, 359
 OSPF. *See* Open Shortest Path First (OSPF) protocol
 Output Queue Length, 526
 overclocking, 87
 oversubscribed server, 41

P

packet internet groper (Ping), 291–292, 556–558
 packetization, SCSI, 195

PAE. *See* Physical Address Extension (PAE), Intel
 page fault, 337
 paging, 337
 paging file, modifying, 367
 PAP. *See* password authentication protocol (PAP)
 parallel bus, 192
 parity, 213–214
 partitions, 177–178, 318, 351–354
 passive cluster, 469
 passive hub, 296
 passive termination, 202
 pass-through termination, 201
 password authentication protocol (PAP), 416
 password protection, 4, 72, 113, 159
 "P" cable, 197
 PCI. *See* Peripheral Components Interface (PCI) bus
 PC servers
 chassis, heavy duty, 24
 cooling fans, 24
 expandability, 24
 hard disks, hot-pluggable, 23
 high voltage differential signaling and, 199
 PCI slots, hot-pluggable, 22
 power supply, 23
 rack mountable, 24–25
 PDC. *See* Primary Domain Controller (PDC)
 PDU. *See* power distribution unit (PDU)
 peer-to-peer (P2P) application, 421
 Pentium III Xeon processors, 245–246, 247
 Pentium models, versus Xeon processor, 100–101
 performance
 of ATA-4, 185
 SCSI, 206, 207
 server, 12–14, 475–476
 processor, 12–13

- performance monitoring and optimization
 - capacity planning, 512–513
 - in general, 495
 - tools, problem solving, 511–512
- performance monitoring and optimization, baseline, 509–511
 - bottleneck defined, 509–510
 - when to create a, 510–511
 - what to monitor, 510–511
- performance monitoring and optimization, hard disk, 521–525
- performance, acceptable, 521–522
- solutions, 522–525
 - controllers, add, 524
 - defragmentation , 523–524
 - disk errors, check, 525
 - file archives, 524
 - file distribution, 524
 - hard disks, add or replace, 522
- performance monitoring and optimization, memory, 518–521
- performance, acceptable, 518–519
- solutions, 519–521
 - applications distribution, 521
 - faster memory use, 520–521
 - memory, additional, 519
 - memory leak check, 521
 - motherboard upgrade, 519
 - swap file size, increase, 519–520
- performance monitoring and optimization, network, 525–528
- performance, acceptable, 526
- solutions, 526–528
 - equipment improvement, 527
 - multihoming, 526–527
 - network interface card, upgrade, 528
 - port or link aggregation, 527
 - server placement, 528
- performance monitoring and optimization, processor, 513–517
- performance, acceptable, 513
- solutions
 - applications and drivers, operation of, 515–516
 - applications, services, movement of, 515
 - clustering implementation, 515
 - compression removal, 514
 - encryption removal, 514
 - process priority, set, 517
 - servers, additional, 514
 - software RAID removal, 515
 - symmetric multiprocessing, 513–514
- performance monitoring and optimization, server, 496–497
- performance monitoring and optimization, tools for, 497–509
 - IBM OS/2, 498
 - Linux/UNIX, 499–501
 - Microsoft Windows 2000, 505–509
 - performance logs and alerts, 506–509
 - System Monitor, 506
 - Microsoft Windows NT 4.0, 503–504
 - Novell NetWare, 501–502
- Performance Monitor, Windows, 502
- Peripheral Components Interface (PCI) bus, 92–97
 - bus mastering, 94
 - intelligent input/output, 96–97
 - interrupts, 94
 - PCI hot swap, 95
 - PCI-X, 93–94
 - peer PCI bus, 95–96
 - slots, hot-pluggable, 22
- peripherals, adding, 543–544
- permissions, security, 11–12
- personal identification number (PIN), 10, 264
- PGA. *See* Pin Grid Array (PGA)
- Phoenix Technologies, BIOS programming, 111–112
- Physical Address Extension (PAE), Intel, 101–102
- physical network topology, 284, 293
- pilot, 241–268
- pilot program, 240
- Ping. *See* packet internet groper (Ping)
- Pin Grid Array (PGA), 246
- PIN number. *See* personal identification number (PIN)
- plenum, defined, 59–60
- point-to-point protocol (PPP), 415
- point-to-point tunneling protocol (PPTP), 415
- POP3. *See* Post Office Protocol 3 (POP3)
- port aggregation, 527
- positive pressure, cooling fans and, 56
- POST. *See* power-on self test (POST)
- Post Office Protocol 3 (POP3), 407
- power. *See also* power supply; server power
 - electrostatic discharge and, 242–243
 - factor, 141
 - rack installation and, 155–158
- power distribution unit (PDU), 134, 155–158
- power management, 115
- power-on self test (POST), 112–113, 553
- PowerQuest DriveImage, 19, 237
- PowerQuest PartitionMagic, 178
- power supply
 - PC servers and, 23
 - requirements, calculating, 134–135
 - server power, 132–134

server, upgrading, 261–267
 multimeter, using, 262–264
 power supply, replacing, 265–267
 troubleshooting, 574
 power supply unit (PSU), 132–134, 265–267
 PPP. *See* point-to-point protocol (PPP)
 PPTP. *See* point-to-point tunneling protocol (PPTP)
 Primary Domain Controller (PDC), 365
 primary partition, 177–178
 printer, 141
 problem solving. *See* troubleshooting and problem determination
 processor. *See also* performance monitoring and optimization, processor
 for mainframe servers, 25–26
 memory and cost effectiveness of, 20
 Microsoft Windows NT 4.0 and, 503–504
 motherboard architecture
 64-bit, 103–104
 AMD Sledgehammer, 104
 Intel Itanium, 103–104
 cache memory, 99–100
 in general, 98
 server processors, 100–103
 speed, 98
 performance, 12–13
 server, upgrading, 245–253
 in general, 245–246
 operating system, notifying, 252–253
 processor cooling, 250–252
 slots and sockets, 246–250
 troubleshooting, 579
 process priority, set, 517
 Promise Technology, 214, 525
 protocols. *See also* network protocols
 Bootstrap Protocol, 390, 393

Dynamic Host Configuration Protocol, 390–393
 email, 407–408
 Open Shortest Path First, 428
 remote access service and, 414–415
 security, 416
 proxy agent, 405–406
 proxy server, 428–429
 ps command, 499
 PSU. *See* power supply unit (PSU)
 pull replication partners, 404
 push/pull replication partner, 405
 push replication partners, 404–405

Q

QAS. *See* Quick Arbitration and Selection (QAS)
 QIC. *See* Quarter Inch Cartridge (QIC)
 Quarter Inch Cartridge (QIC), 452–455
 query, iterative, 395–396
 query, recursive, 394–395
 queuing, command, 193
 Quick Arbitration and Selection (QAS), 195

R

rack installation. *See* server rack installation
 Radio Electronics Television Manufacturers Association (RETMA), 146
 RAID. *See* Redundant Array of Independent Disks (RAID)
 RAM
 interleaving, 108–110
 memory modules and, 104–108
 memory performance and, 519–521
 server processor and, 12–13
 Rambus DRAM (RDRAM), 107, 256
 Rambus Technology, RDRAM creator, 107

RAS. *See* Remote Access Server (RAS); remote access service (RAS)
 RDRAM. *See* Rambus DRAM (RDRAM)
 reboot, partition creation and, 177
 receptacle tester, 64–65
 records, Domain Name Service, 398–400
 recursive query, 394–395
 Red Hat Disk Druid, 351, 352–354
 Red Hat Linux, 349, 350, 351–354, 570
 reduced instruction set computing (RISC) processor, 22
 redundancy
 defined, 7
 IDE/ATA and, 191
 RAID and, 211–212
 SCSI, 206
 Redundant Array of Independent Disks (RAID)
 hard disk performance and, 522
 RAID-0, 210–211
 RAID-0+1, 212–213
 RAID-1, 211–212
 RAID-5, 213–214
 software RAID vs. hardware RAID, 215
 software removal, 515
 troubleshooting, 576–578
 cabling, 577
 device ID, 577
 RAID, 578
 termination, 576
 registered jack-45 (RJ-45), 303
 registered jack-45 (RJ-45) connectors
 how to cut and crimp, 306–310
 network cabling, 305
 troubleshooting, 552
 registered memory, 110
 remote access, applications, 17
 Remote Access Server (RAS), 17

remote access service (RAS)
 configuring on a server,
 416–417
 in general, 413–414
 and network operating systems,
 413–416
 protocols support, 414–415
 and security protocols, 416
 remote administration mode, 566
 remote monitoring (RMON), 425
 remote user, 17
 remote work, troubleshooting,
 565–569
 administration tools for, 566–569
 in general, 565–566
 repeater placement, 297
 replication, 403, 404–405
 replication interval, 404
 replication trigger, 404
 re-tension, tape, 459
 RETMA. *See* Radio Electronics
 Television Manufacturers
 Association (RETMA)
 reverse lookup zone, 398
 ring topology, 285–287
 RIP. *See* Router Information
 Protocol (RIP)
 RISC (reduced instruction set
 computing) processor, 22
 Ritchie, Dennis, 347
 RJ-45. *See* registered
 jack-45 (RJ-45)
 RMON. *See* remote
 monitoring (RMON)
 round trip time (RTT), 292
 Router Information Protocol
 (RIP), 426–427
 routers, 50, 300–301
 router, server as a, 426–428
 Open Shortest Path First proto-
 col, 428
 Router Information Protocol,
 426–427
 routing loops, 427
 RTT. *See* round trip time (RTT)
 run time, UPS and, 141

S

SAN. *See* storage area
 network (SAN)
 scope, defined, 392–393
 SCSI. *See* Small Computer
 Systems Interface (SCSI)
 SDRAM. *See* synchronous
 dynamic RAM (SDRAM)
 SECC. *See* Single Edge Contact
 Cartridge (SECC)
 SECC2. *See* Single Edge Contact
 Cartridge2 (SECC2)
 Secure Sockets Layer (SSL), 411
 security. *See also* disaster planning
 authentication and, 8–11
 boundaries of, 12
 for client-server networks, 6
 DHCP server and, 393
 for FAT, 179
 firewalls and, 428–429
 in KVM, 159
 monitoring, 473
 peer-to-peer networks and, 4–5
 permissions, 11–12
 protocols, 416
 server planning
 disaster planning, 67–69
 secure location for, 71–74
 server room access, 72–74
 staff and, 72
 SNMP and, 472
 security guard, 73–74
 segments, SCSI, 206
 Self Monitoring and Reporting
 Technology (S.M.A.R.T.),
 184, 525
 Semiconductor Reliability
 News, 242
 serial line internet protocol
 (SLIP), 415
 server. *See also* disaster planning;
 troubleshooting and problem
 determination
 Domain Name Service and,
 400–401

 as a firewall, 428–429
 in general, 2
 interaction, 545
 messages, 546–549
 monitoring, 496–497
 N+1 expandability, 133, 140
 placement of, 47–51, 528
 processor performance moni-
 toring, 514
 purpose, 545–546
 as a router, 426–428
 Open Shortest Path First pro-
 tocol, 428
 Router Information Protocol,
 426–427
 work statement, 546
 server classes, 22–26
 mainframe, 25–26
 bus speed, 26
 cost, 25
 durability, 26
 memory, 26
 processors, 25–26
 size, 25
 storage, 26
 minicomputer, or midrange
 computer, 26
 PC servers, 22–25
 chassis, heavy duty, 24
 cooling fans, 24
 expandability, 24
 hard disks, hot-pluggable, 23
 PCI slots, hot-pluggable, 22
 power supply, 23
 rack mountable, 24–25
 server functions, 8–21
 applications access, 15–17
 database applications, 16
 email services, 16
 network management soft-
 ware, 16–17
 remote access, 17
 virtual private networks, 17
 centralized management, 18
 cost effectiveness, 18–21
 processors and memory, 20

- savings, efficiency, and productivity, 21
- storage, 19
- performance, 12–14
 - hard disk, 13–14
 - access time, 14
 - buffer cache, 14
 - interface, 14
 - multiple, 14
 - processor, 12–13
 - Cache, 13
 - clock speed, 12
 - Data bus, 13
- security, 8–12
 - authentication, 8–11
 - boundaries of, 12
 - permissions, 11–12
- services, 8
- storage capabilities, 15
- server, Peer-to-Peer and Client-Server Models
 - Client-Server, 6–8
 - in general, 2
 - Peer-to-Peer, 3–6
- server placement, 47–51
 - in general, 47–48
 - inter-site, 50–51
 - intra-site, 49–50
- server planning, 62–67
 - business purpose, 40–42
 - expense versus savings, 41
 - expertise for, 42
 - need for server, 40–41
 - purchase, timing, 41
- disaster planning
 - fire detection and suppression, 67–68
 - flood considerations, 68–69
- for interoperability, 43–47
- network diagram creation, 51–52
- power supply
 - availability of, 62–64
 - electromagnetic interference, 65–67
 - quality of, 64–65
- secure location, 71–74
 - access to server room, 72–73
 - bio-recognition, 73
 - card scanners, 73
 - keypad, 73
 - access to server room, monitoring, 73–74
 - logs, 74
 - security guard, 73–74
 - sign-in, 73
 - video surveillance, 74
- staff and, 72
- site readiness
 - air quality, 55–56
 - flooring, 58–62
 - in general, 52–53
 - humidity, 56–57
 - temperature, 53–55
- space usage and, 69–71
 - avoid exterior windows and walls, 70
 - budget for server room
 - design, 70
 - central location, 69
 - consolidate space, 69
 - foot traffic restriction, 69
- user demand, 42–43
- server power, 131–143
 - power supply, 132–134
 - requirements, calculating, 134–135
- uninterruptible power supply (UPS), 136–143
 - architectures of, 136–137
 - failover for, 139–140
 - requirements for, determining, 140–141
 - site preparation, 141–143
 - software for, 139
 - UPS operation, 138–139
- server processors, 100–103
- server rack installation, 144–160
 - configuration of, 149–155
 - cable management, 152–155
 - device grouping, 151–152
- KVM (single keyboard, video display, and mouse), 158–160
- power, 155–158
 - tips for, 160
 - vendors of, 149
 - weight distribution, 150–151
- cooling, 147–148
- physical characteristics of, 144–146
 - height and depth, 145
 - units, 144–145
 - width and weight, 146
- server upgrade, performing, 241–268
 - adapters, upgrading, 267–268
 - BIOS, recovering, 260–261
 - BIOS, updating, 259–260
 - electrostatic discharge, avoiding, 241–245
 - chassis, touch, 242
 - grounding kit, use, 243
 - other tips for, 244–245
 - power, unplug, 242–243
- memory, upgrading, 253–259
 - identification of, 254–256
 - installation of, 257–259
- power supply, upgrading, 261–267
 - multimeter, using, 262–264
 - power supply, replacing, 265–267
- processor, upgrading, 245–253
 - in general, 245–246
 - operating system, notifying, 252–253
 - processor cooling, 250–252
 - slots and sockets, 246–250
- UPS, upgrading, 268–269
- server upgrade, preparation for, 232–240
 - inventory, making an, 239–240
 - notifying users, 234–235
 - planning for failure, 236–237
 - systems, resources, verifying, 237–239
 - upgrade components, 235–236
 - when to upgrade, 232–234

- server upgrade, test and pilot, 240–241
 - services
 - distribution of, 521
 - processor intensive, moving, 515
 - server functions, 8
 - servo mechanism, 176
 - shielded twisted-pair (STP) network cable, 65–66, 302–303
 - Shiva password authentication protocol (SPAP), 416
 - shutdown, proper
 - for Linux, 354–355
 - for Microsoft Windows 2000, 373–374
 - for Microsoft Windows NT Server, 367–368
 - for network operating system, 338
 - for OS/2, 359
 - signaling, 199–201
 - SIMM. *See* single inline memory modules (SIMM)
 - Simple Network Management Protocol (SNMP)
 - disaster planning and, 447
 - in general, 407, 422–425
 - settings, 471–472
 - Single Edge Contact Cartridge (SECC), 247
 - Single Edge Contact Cartridge2 (SECC2), 247
 - single inline memory modules (SIMM)
 - digital modem pool and, 317
 - in general, 104–105
 - memory installation and, 257
 - single keyboard, video display, and mouse (KVM), 146, 158–160
 - single-user mode, 354
 - site management, server, 478–479
 - six-cartridge backup, 465–466
 - 64-bit processor, 103–104
 - AMD Sledgehammer, 104
 - Intel Itanium, 103–104
 - slack, defined, 179
 - slave drive, 189–190
 - SLIP. *See* serial line internet protocol (SLIP)
 - slots, processor, 246–250
 - Small Computer Systems Interface (SCSI)
 - backup and, 450
 - controllers, adding, 524
 - hard disks and, 14
 - RAID and, 211
 - S.M.A.R.T. and, 184
 - troubleshooting, 576–578
 - cabling, 577
 - device ID, 577
 - RAID, 578
 - termination, 576
 - troubleshooting and, 553
 - Small Computer Systems Interface (SCSI), configuration, 196–207
 - drive configuration (SCSI ID and LUN), 203–206
 - SCSI ID assignment, 205–206
 - topology, 204–205
 - pros and cons of, 206–207
 - SCSI cables and connectors, 196–199
 - SCSI termination, 201–203
 - signaling, 199–201
 - high voltage differential, 199–200
 - low voltage differential, 200–201
 - single-ended, 199
 - Small Computer Systems Interface (SCSI), ID, 195, 205–206
 - Small Computer Systems Interface (SCSI), interface, 192–196
 - SCSI-1, 192–193
 - SCSI-2, 193
 - SCSI-3, 193–196
 - SPI-2, 194
 - SPI-3, 194–195
 - SPI SCSI-3 Parallel Interface, 194
 - Ultra160 and Ultra160+, 195–196
 - S.M.A.R.T. (Self Monitoring and Reporting Technology), 184
 - Smart Drive caches, 362
 - smoke alarms, 67–68
 - SMP. *See* symmetric multiprocessing (SMP)
 - snagless boot, 308–309
 - SNAS. *See* Systems Network Architecture Server (SNAS)
 - SNMP. *See* Simple Network Management Protocol (SNMP)
 - sockets, processor, 246–250
 - software programs
 - for backup, 459–460
 - for cloning, 572
 - installing and troubleshooting, 544
 - to monitor storage use, 15
 - RAID, 215
 - RAID removal, 515
 - for server management, 472–474
 - for UPS, 139
 - SONET ring, 412
 - South Bridge chipset, 89–91
 - space use, server room, 69–71, 144, 159
 - SPAP. *See* Shiva password authentication protocol (SPAP)
 - spare parts, 470–471
 - speed, connection, 49–50, 285
 - speed, processor, 98
 - SPGA. *See* Staggered Pin Grid Array (SPGA)
 - SPM/2. *See* System Performance Monitor/2 (SPM/2)
 - SPS, standby power supply (SPS)
 - SSL. *See* Secure Sockets Layer (SSL)
 - stabilizing feet, 146
 - Staggered Pin Grid Array (SPGA), 246
 - stand-alone Server, 365
 - standby/offline, UPS type, 136
 - standby power supply (SPS), 136–137
 - Start of Authority server, 397
 - star topology, 287–288
 - static IP address, 390
-

- static load balancing, 469
 - stepping, defined, 246
 - storage
 - of backups, 460–461
 - cost effectiveness, 19
 - in general, 15
 - mainframe servers and, 26
 - NetWare and, 181–182
 - network attached, 208
 - server, 15, 19
 - storage area network (SAN), 208, 210
 - StorageTek L7000, tape
 - backup, 452
 - STP cable. *See* shielded twisted-pair (STP) network cable
 - stripping tool, Universal UTP, 307
 - subnet mask, 290
 - subnets, 50
 - Sun Microsystems, 22, 104
 - superscalar, defined, 12
 - SuSE Linux, 349
 - Sutton Designs website, 143
 - swap-file space
 - memory and, 519–520
 - for Microsoft Windows 2000, 373
 - for Microsoft Windows NT Server, 367
 - for OS/2, 359
 - virtual memory and, 337
 - swapping, 337
 - switched fabric, defined, 209
 - switches, Ethernet, 299–300
 - switching hub, 296
 - switch, local area network and, 2
 - Symantec Ghost, GDISK and, 178
 - Symantec pcAnywhere, 566
 - symmetric multiprocessing (SMP)
 - defined, 13
 - implementation, 514–514
 - processor performance monitoring, 513–514
 - processor upgrading and, 245
 - synchronize, defined, 41
 - synchronous dynamic RAM (SDRAM), 106, 254–256, 520–521
 - system clock, 559
 - system diagnostic utilities, 562–565
 - System Performance Monitor/2 (SPM/2), 498
 - system resources, verifying, 237–239
 - Systems Network Architecture Server (SNAS), 420–421
- T**
- tape backup, 449–450
 - tape backup, automated, 451–459
 - in general, 451–452
 - maintenance of, 458–459
 - types of, 452–458
 - Advanced Intelligent Tape, 455
 - digital audio tape, 454–455
 - digital linear tape, 455–456
 - Quarter Inch Cartridge, 452
 - Travan, 452–454
 - Ultrium tape, 456–458
 - tape library, 451–452
 - TCP/IP. *See* Transmission Control Protocol/Internet Protocol (TCP/IP)
 - TDR. *See* time domain reflectometer (TDR)
 - telephone, 315–318, 581
 - Telnet utility, 159–160
 - temperature
 - hard drives and, 176
 - server and, 53–55
 - server maintenance and, 475–476
 - tape media and, 458
 - 10BaseT, network cabling, 287, 311
 - termination, SCSI, 201–203, 576
 - terminator, defined, 201
 - test, server upgrade, 240–241
 - thermal tape, 252
 - thermostat, 54
 - thicknet cabling, 301
 - thin client, defined, 20
 - thin-film magnetic medium, 175
 - thinnet cabling, 301–302
 - Thompson, Ken, 347
 - thread, defined, 513
 - throughput, 13, 89
 - time domain reflectometer (TDR), 555–556
 - token passing, 286
 - Token Ring network, 288, 295
 - toner generator and locator, 556
 - top command, 499–500
 - topology, network. *See* network topologies
 - Torvalds, Linus, 348
 - Tower of Hanoi backup method, 466–467
 - TRACERT utility, 293–294, 558
 - Traffic Manager, Novell NetWare, 501–502
 - transceiver, ring topology, 286
 - transistor, defined, 53
 - Transmission Control Protocol/Internet Protocol (TCP/IP)
 - Address Resolution Protocol, 293
 - Internet Address, 290
 - IPCONFIG utility, 292–293
 - NETSTAT, 294
 - packet internet groper, 291–292
 - server access and, 43
 - subnetting the network, 291
 - TRACERT utility, 293–294
 - Travan (tape media), 452–454
 - Travan NS, 453–454
 - Tripp-Lite, 139, 143, 144
 - troubleshooting and problem determination, 541–580
 - booting unbootable server, 569–571
 - connections, physical, 552–553
 - connections, 552–553
 - network cabling, 552
 - diagnostic tools, 555–565
 - connectivity utilities, 556–558
 - network cable diagnostic devices, 555–556
 - operating system utilities, 559–562

- Linux, 560–561
 - Microsoft Windows 2000, 562
 - Microsoft Windows NT 4.0, 561
 - Novell NetWare, 560
 - OS/2, 559
 - system and hardware diagnostic utilities, 562–565
 - drastic measures, 572
 - field replaceable units, 573–579
 - adapter cards, 578–579
 - hard disks, 575–576
 - memory, 574–575
 - power supply, 574
 - processor, 579
 - SCSI and RAID, 576–578
 - cabling, 577
 - device ID, 577
 - RAID, 578
 - termination, 576
 - in general, 542
 - help, getting, 580–581
 - problem investigation, 542–551
 - documentation, 543
 - log records, check, 543–546
 - cable labeling, 546
 - hardware and drivers, installing, 544–545
 - new peripherals, adding, 543–544
 - server interaction, 545
 - server purpose, 545–546
 - server work statement, 546
 - software, installing, 544
 - updates or upgrades, installing, 544
 - user identification, 546
 - procedures for, 549–551
 - server messages, check, 546–549
 - remote work, 565–569
 - administration tools for, 566–569
 - in general, 565–566
 - tips for, 579–580
 - using your senses, 554–555
 - viruses, 572–573
 - true power, 141
 - trust, defined, 12
 - tunneling protocols, 415
 - turnkey fax servers, 418
- U**
- Ultra SCSI, 194
 - Ultrium (tape media), 456–457
 - Uniform Resource Locator (URL), 8
 - uninterruptible power supply (UPS)
 - capacity and runtime, 545
 - power availability and, 62–63
 - rack installation and, 155
 - server power, 136–143
 - architectures of, 136–137
 - failover for, 139–140
 - requirements for, determining, 140–141
 - site preparation, 141–143
 - software for, 139
 - UPS operation, 138–139
 - server, upgrading, 268–269
 - weight of, rack configuration and, 150
 - UNIX
 - performance monitoring and optimization, 499–501
 - server interoperability and, 45
 - UNIX file system, 181
 - UNIX/Linux, configuring, 347–355
 - in general, 347–348
 - Linux
 - hardware requirements, 349–350
 - installation of, 350–354
 - shutdown, proper, 354–355
 - versions, 349
 - unshielded twisted-pair (UTP) network cable, 304–305
 - updating network operating system, 374–375
 - upgrade. *See also* server upgrade, performing
 - to Microsoft Windows 2000, 372–373
 - to Microsoft Windows NT Server, 366
 - of motherboard, 519
 - for network operating system, 337–338
 - to OS/2 Warp, 359
 - of processor, 245
 - troubleshooting and, 544
 - UPS. *See* uninterruptible power supply (UPS)
 - uptime, defined, 24
 - UPTOMB utility, 253
 - URL. *See* Uniform Resource Locator (URL)
 - user demand
 - number of users, 42
 - user access, direct, 43
 - user access, nature of, 43
 - users
 - authentication of, 9–10
 - identification of, 546
 - input for troubleshooting, 550
 - modem pool and, 316–317
 - notification of server upgrade, 234–235
 - permissions for, 11–12
 - security and, 12
 - utilities
 - for connectivity, 556–558
 - for disk defragmentation, 524
 - IPCONFIG, 292–293
 - operating systems, 559–562
 - system and hardware, 562–565
 - TRACERT, 293–294, 558
 - UPTOMB, 253
 - UTP. *See* unshielded twisted-pair (UTP) network cable
-

V

velocity of propagation (VOP), 556

vendors. *See also* websites

- of grounding kits, 244
- Microsoft Windows 2000 and, 545
- of server management programs, 239
- of server racks, 149
- server upgrade and, 236

video monitor, 158–160

video surveillance, 74

virtual memory/swap files, 337

Virtual Private Network (VPN), 17, 413–414

virus, backups and, 462

virus, troubleshooting, 572–573

Visio 2000, 52

vmstat command, 499

voice coil, actuator mechanism, 176

volume, NetWare and, 181

VOP. *See* velocity of propagation (VOP)

VPN. *See* Virtual Private Network (VPN)

W

wake-on LAN (WOL), 565–566

wake-up packet, 565

WAN. *See* wide area network (WAN)

warning light, 132–133

wattage, server power, 134–135

web and FTP servers, 410–413

- configuring, 413
- requirements, 410–413

web farm, defined, 42

websites

- for AGP cards, 97
- for ATA/IDE, 191
- for boot disks, 571

- for cables, 306, 553
- for chipsets, 88
- for disaster recovery services, 477
- for disk defragmentation utilities, 524
- for electrical information, 63
- for grounding kits, 244
- for halon substitutes, 68
- for interleaving, 108
- for memory modules, 110
- for Novell NetWare 5.1, 347
- for OS/2 information, 359
- for overclocking, 87
- for PCI, 93
- for rack configuration, 149
- for rack installation, 160
- for raised floors, 61
- for SCSI equipment, 577
- for SCSI standards, 196
- for server management, 239, 473
- for UPS equipment, 143
- for virus protection, 573
- for Windows NT Server 4.0, 361

WebSphere, IBM, 341

web support, 581

weight distribution, rack, 146, 150–151

wheels, rack, 146

wide area network (WAN)

- defined, 2
- server placement and, 48, 50–51
- WAN link, 41

wide SCSI, 193

Wide Ultra SCSI, 194

width, rack, 146

Windows 2000. *See* Microsoft Windows 2000

Windows 2000 Advanced Server. *See* Microsoft Windows 2000 Advanced Server

Windows 2000 Server.

See Microsoft Windows 2000 Server

Windows 95/98. *See* Microsoft Windows 95/98

Windows Internet Naming Service (WINS), 401–406

- in general, 401–402
- NetBIOS names, resolving, 402–403

proxy agent, 405–406

pull replication partners, 404

push/pull replication partner, 405

push replication partners, 404–405

replication, 403–404

Windows .NET. *See* Microsoft Windows .NET

Windows NT. *See* Microsoft Windows NT

WINS. *See* Windows Internet Naming Service (WINS)

WOL. *See* wake-on LAN (WOL)

workstations, defined, 3

X

X.500 ITU standard, 339

Xeon processor, 100–101, 245–246, 247

X Term session, 354

X Windows, graphical user interface, 347

Z

Zero Effort Networks (Z.E.N.), NetWare, 339

zero insertion force (ZIF), 248–249

zones, Domain Name Service, 397–398

